Vivitar

ViviCam 8600s

8.1 Mega Pixel CCD, 6X Optical Zoom Image stabilization. Focus to 2cm in macro

Slim type camera w/ unlimited video clip

2.8 inch LTPS TFT LCD

MPEG 4 Audio & Video Support

IMAGE SENSOR

DIMENSIONS

USB 2.0 High speed & PictBridge Support





•	IIII/ COL CLICOIC	8.1 Mega pixer 1/1.8 inch CCD
•	COLOR	24-bit Color (RGB)
•	IMAGE RESOLUTION	Still: 3264x2448, 2560x1920, 1600x1200 , 640x480 (File format: JPEG) Movie clip: 640x480 @ 30fps , MPEG 4(ASP)
•	LENS	Auto Focus Lens
		-Aperture: F= 2.8(W) ~ 4.8(T)
		-Focus Range: Macro: 2cm ~infinity. (Wide)
		0.5m ~ infinity. (Tele)
		Normal: 0.5m ~ infinity (Standard)
		-Effective Focal Length: 7.8mm ~46.8mm (37~222mm in
		35mm)
•	Digital ZOOM	1x~ 8.0x (in still Capture mode), 2x, 4x, 8x, (in still Playback mode)
•	SHUTTER SPEED	Normal: 4sec ~1/1500 sec (Electronic Shutter)
•	DIAL MODES	Auto / Program / Av / Tv / Manual / Portrait / Sport / SCN / Movie, /Panorama
•	EXPOSURE COMPENSATION	Manual: -2.0 ~ +2.0 EV in 1/3EV steps,
•	WHITE BALANCE	Auto, Manual: Daylight, Incandescent, Fluorescent 1, Fluorescent 2, Cloudy,
•	LCD DISPLAY	Display: 2.8 " color LTPS-TFT LCD (230 K resolution)
		LCD Status Icons: Focus/AE/Photometry/White Balance/Shot mode/SD Card status/image quality/ Flash/ ISO/EV/Self timer/Digital zoom//Battery Status/Number of Images/Scene program, etc.
•	MEMORY	Internal: None
		External: Secure Digital Card up to 1GB
		Quality: Fine/Standard/Economy
	Mayia and Audia	Movie: 640x 480, recording until media is full.
•	Movie and Audio	Audio: After recording and voice memo: 30 sec.
	FLAGU	With microphone and speaker
•	FLASH	Built-In: Auto, Flash On, Flash Off, Red-Eye Reduction
	SELF-TIMER	10 sec, 2 sec, 10+2sec.
•	FILE FORMAT	JPEG (EXIF 2.2), DCF, AVI, TIFF
•	OPERATING	PC: Windows 98/98SE/2000/ME/XP
	ENVIRONMENT	Mac: OS 9.0 or later
	SOFTWARE	Driver: USB Mass Storage for PC and Mac
	LANGUAGE CURRORT	AP: Photo Explorer 8.0 and Photo Express 5.0 (Windows)
•	LANGUAGE SUPPORT	English, German, French, Spanish, Traditional Chinese, Simplified Chinese, Italian
•	CONNECTORS	AC-DC Adapter port, USB 2.0, A / V Output (NTSC/PAL selectable)
•	POWER	Lithium-ion rechargeable battery 3.7V (included)
		AC-DC Adapter 5V, 3A (included)
•	CERTIFICATION	CE, FCC, VCCI, BSMI
•	WEIGHT	150g 5.3 oz (without battery or SD card)

8.1 Mega pixel 1/1.8 inch CCD

Design and Specifications are subject to change without notice.

93 x 57x 25.5 mm (3.7 x 2.3 x 1 in)